

260 PROSTOP SPEED



Cement Based Fast Setting Water Plug Powder

PRODUCT DESCRIPTION

It is a cement-based, very fast-setting, mineral-filled, water-impermeable, single-component shock water plug powder used in powder form containing special chemical additives.

FEATURES

It prevents active water leaks and leaks in 5-10 seconds.

It has water repellent properties. It hardens quickly.

It expands against the direction of water flow and cuts off the flowing water.

Provides water repellent barrier.

It prevents iron reinforcement from corroding.

PRODUCT INFORMATION

Chemical Structure Cement based
Appearance / Color Powder / Gray

PERFORMANCE

(23°C, 50% Relative Humidity)

Dry Bulk Density (powder component)	1350 ± 200 kg/m ³	TS EN 1015-10
Compressive strength (28 DAYS)	30 N/mm ²	TS EN 196-1
Coating on during time	3-5 min	

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. Values may change as temperature and humidity values in the construction site environment and application surfaces and areas will vary.

USAGE AREAS

Rapid shut-off of pressurized water.

Stopping active water leaks and leaks.

In foundations, elevator shafts.

It is used to repair holes in concrete pipes.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

260 PROSTOP SPEED



Cement Based Fast Setting Water Plug Powder

APPLICATION INSTRUCTIONS

Surface; It must be cured, moist and solid. It should be removed from residues such as oil, grease, dirt and paint that would prevent adhesion. If active water leakage comes from thin cracks, the cracks should be broken and widened to reduce water pressure.

Protective gloves should be used before starting the application. BARS PROSTOP SPEED Water Cutting Shock Powder is used directly in powder form.

Take a heaping amount of powder into your palm and harden it in your palm with both hands. It is pressed towards the source of water leakage in one move. Pressing is continued until the water flow stops. After the water is cut off and set, it is left and the surface is roughened with a brush. It is waterproofed with BARS Mineral Based Waterproofing Systems. Opened product should be used within 1 week. Otherwise, efficiency cannot be obtained. Expired mortar must be disposed of.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. The surface temperature during application should be between +5 °C and +30 °C. Application should not be made on surfaces at risk of frost. Since the product is rigid, additional precautions should be taken in areas that will be exposed to vibration.

PACKAGING

5kg plastic bucket
10 kg plastic bucket

SHELF LIFE

It is 6 months from the date of production in its original, unopened package, in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

260 PROSTOP SPEED



Cement Based Fast Setting Water Plug Powder

SAFETY

Since it is cement based, do not breathe the dust, use a mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, rinse with plenty of water and consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test the suitability of the product before using it.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com