

981 PROFACADE PRIMER



Thermal Insulation Coating Primer

PRODUCT DESCRIPTION

It is an acrylic copolymer emulsion based, white colored primer with high adherence strength, developed for pre-coating in heat insulation systems.

FEATURES

- It facilitates patterning during PROKREPI and PROCOLOR application.
- It prevents surface dirt and stains from appearing on the PROKREPI coating..
- It has high closing power. Hardens the application surface.
- It reduces the water absorbency of the surface. Makes the surface homogeneous for coating.
- It is matte white in color .

USAGE AREAS

It is used before coating applications on thermal insulation systems and on previously painted or unpainted exterior and interior surfaces .

APPLICATION EQUIPMENT

Roller, brush, spray



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

Thermal Insulation Coating Primer

APPLICATION INSTRUCTIONS

The surfaces on which Coating Primer will be applied must be dry and free from all kinds of contamination. The primer is applied directly by brush, roller or spraying. Mix before application. During application, make sure that the surface and air temperature is between +5°C and +30°C. Do not apply on very hot surfaces exposed to rain, strong breezes or direct sunlight. We recommend that you apply it in a single coat, 1 day before the coating application. The primer is produced in white color. If the color tone is desired, BARS COLORA TE coloring tubes can be used to ensure that it is suitable for the coating color to be applied.

LIMITATIONS

Initial Drying at 20°C and HR: 65%: 1 hour; Final Drying: 24 hours, Coating application is made after 12 hours .

CONSUMPTION

Coating Primer 100-200 gr/m² in a single layer. It should be taken into consideration that the specified consumption amounts may vary depending on the surface and application conditions.

PACKAGING

15 kg plastic bucket.

SHELF LIFE

It can be stored for 1 year in unopened packaging, in a cool place, protected from direct sunlight and frost.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.

981 PROFACADE PRIMER



Thermal Insulation Coating Primer

SAFETY

Do not inhale the product and do not contact it with skin or eyes. Use protective gloves, glasses and clothing. In case of eye contact, rinse with plenty of water and consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test the suitability of the product before using it.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com