

Anti Mold and Moisture Paint

PRODUCT DESCRIPTION

It is a very strong insulation paint containing acrylic resin-based solvent, modified with special chemicals and polymers, to eliminate moisture and mold problems arising from natural conditions on the interior and exterior walls of buildings.

FEATURES

PROMOLD prevents the formation of mold in its dry film on the surface it is applied to.

It has high covering power.

It has high adherence. It is matte. It is easy to apply.

It can be painted over.

PRODUCT INFORMATION

Chemical Structure Acrylic resin based / Solvent based

Appearance / Color Liquid / White

PERFORMANCE

(23°C, 50% Relative Humidity)

Brightness G3 TS 4318 EN ISO 2813

Grain Size S1 TS 2620 EN ISO 1524

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. The values may change as the temperature and humidity values in the construction site environment and the application surfaces and areas will vary.

USAGE AREAS

On interior and exterior walls,
In basements, garages or cellars,
On interior walls facing north,
Darkening and mold on all walls
It is used in areas where there is a lot of moisture and humidity.

805 PROMOLD



Anti Mold and Moisture Paint

APPLICATION INSTRUCTIONS

Surface; It must be cured, dry and sound. It should be cleaned of any residues such as oil, grease, dirt, paint, salt vomit that would prevent adhesion. Necessary repairs must be made to all cracks, joints, skirts and damaged leakage areas. The resulting molds are cleaned mechanically. After the surface is completely dry, PROMOLD application is started. The product is ready to use, it is not diluted with any other material. Mix with a low speed mixer and apply in two layers with a roller or brush. After the first coat, wait 4-6 hours for it to dry and then apply the second coat. If desired, it can be painted with a different color .

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should not be made in very high temperatures, direct exposure to sunlight, very windy or rainy weather. Application should not be made on surfaces at risk of frost. Application should be made between +5 C and +30 C. Application should never be made at temperatures below 5 C. The product should be protected from rain, water, frost and negative external factors until it cures.

CONSUMPTION

200-300 gr / m²

PACKAGING

0,750 ml Tin

5 kg Tin

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use.

It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

805 PROMOLD



Anti Mold and Moisture Paint

SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, rinse with plenty of water and consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet .

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products, and it is a recommendation and this information is about correct application ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test the suitability of the product before using it.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com