

Siliconized Acrylic Sealant

PRODUCT DESCRIPTION

It is a silicone-added, acrylic dispersion-based, single-component, general-purpose mastic resistant to outdoor weather conditions.

It is an ideal, economical joint filling mastic for static joints of building elements.

FEATURES

It is single component, easy to apply and can be used on all porous surfaces (such as brick, concrete, wood). It does not contain solvents, isocyanates and is odorless. It can be painted after drying. It is resistant to weather conditions. It is water based and easy to clean.

PRODUCT INFORMATION

Chemical Structure: Silicone Acrylic Based

USAGE AREAS

It is used in interior and exterior spaces, window, wooden and PVC joinery installation, window sealing areas, and skirting boards.

PERFORMANCE

(23°C, 50% Relative Humidity)

Appearance: High viscosity siliconized acrylic sealant

Intensity : 1,60 0,05 g/cm³ (DN 534)

Application Temperature: +5°C to +30°C Surface Drying Time: 80 - 30 minutes

Elongation at Break: ≥ 150% (28 days)

Curing time: 2 mm / 24 hours

Service Temperature: -10°C / +80°C

These values were obtained as a result of laboratory experiments and are valid for the performance of finished applications at the end of the full drying period. The values may change as the temperature and humidity values in the construction site environment and the application surfaces and areas will vary.

APPLICATION INSTRUCTIONS

The cartridge mouth is cut to allow the insertion of the tip supplied with the cartridge. The tip is attached to the cartridge mouth and, taking into account the width of the area to be used, is cut at a 45° angle with a sharp utility knife and inserted into the cartridge gun. After the product is applied with a gun, the surface is smoothed with a smoothing tool of appropriate width. This process will ensure better adhesion of the mastic and a better filling appearance. Masking tape should be removed within 5 minutes at the latest after the application is completed. Material that gets on unwanted areas should be cleaned with a damp and clean cloth within 5 minutes at the latest. If this period has been exceeded and curing is completed, cleaning can only be done mechanically.

1067 PROSILICONE MASTIC C €



Siliconized Acrylic Sealant

LIMITATIONS

Avoid application at temperatures below +5°C and above +35°C. Not suitable for aquarium applications. It should not be used in completely closed areas as it requires moisture in the air to cure. Not suitable for medical or pharmacological applications. Does not retain paint

PACKAGING

500 gr

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. Values may vary as temperature and humidity values in the construction site environment and application surfaces and areas will vary.

SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses, mask and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. Avoid skin contact. Do not swallow. Keep away from flame sources. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com