

Ceramic Transition Primer

PRODUCT DESCRIPTION

It is a water-based, acrylic polymer-based, ready-to-use transition primer containing special aggregate that increases surface strength by roughening the surface in ceramic-on-ceramic applications and tile-on-tile applications.

FEATURES

- Single component.
- It is based on riding.
- It is easy to use.
- Ready to use.
- It makes the surface rough thanks to the special fillings it contains.
- In tile-on-tile applications, it roughens the surface and increases the surface strength.
- It has high adherence.

PRODUCT INFORMATION

- Chemical structure : Acrylic based / Water based
- Aggregate Structure : Basalt
- Appearance/Color : Liquid / Green

PERFORMANSCE

(23°C, 50% Relative Humidity)

- Ph : 7-10
- Intensity : $140 \pm 0.2 \text{ g / cm}^3$
- Grain Size : S4 TS 2620 EN ISO 1524

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. The values may change as the temperature and humidity values in the construction site environment and the application surfaces and areas will vary.

USAGE AREAS

It is used in ceramic-on-ceramic bonding, before the application of ceramic adhesive, to increase surface adherence. It is recommended to sand the ceramic surface to be applied before use.

Ceramic Transition Primer

APPLICATION INSTRUCTIONS

Surface; It must be cured and solid. Remains such as loose surface, mortar, concrete pieces are cleaned and the surface is strengthened. It should be cleaned of any residues such as oil, grease, dirt, paint, salt vomit that would prevent adhesion. It is recommended to sand the tiles to be applied.

It is ready for use.

APPLICATION EQUIPMENT

Hand mixer - Roller

PROJEL PR is ready for use. The product is mixed at 400-600 rpm with the help of a medium speed mixer. It is mixed quickly until it becomes a homogeneous mixture. It should be applied to the surface with a roller, brush and appropriate spraying equipment. It should be mixed occasionally during application. The surface temperature during application should be between +5 °C and +30 °C. Application should not be made on surfaces at risk of frost. Additionally, application should not be made in extremely hot, rainy or windy weather. After application, it should be protected from direct water contact and frost for 24 hours. Before starting tile-on-tile applications, the primer must be allowed to dry for at least 24 hours. Otherwise, poor adherence may occur.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product should be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

It depends on the surface.

PACKAGING

3kg plastic bucket

15 kg plastic bucket

SHELF LIFE

It is 1 year from the date of production in its original packaging with the lid closed, in a dry and moisture-free environment, away from direct sunlight, at a temperature of +5 - 25 C and 50% relative humidity. The lids of the packages should be closed tightly when not in use. It should be kept away from moisture. Protect from high temperatures and frost.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a dry, cool and moisture-free environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.

870 PROJEL PR



Ceramic Transition Primer

SAFETY

Do not inhale, use mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. of children

Keep it out of reach. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test the suitability of the product before using it.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com