

503 PROREPAIR SPEED



Fast Drying High Strength Repair and Filling Mortar

PRODUCT DESCRIPTION

It is a cement-based, polymer-modified, high-strength and high-performance, fast-drying, resistant to sudden temperature changes, fine-grained, smooth surface repair and filling mortar.

FEATURES

It dries very quickly and can be processed after 30 minutes.

It has high adherence.

It is easy to prepare and apply.

It does not sag on vertical surfaces.

It does not cause shrinkage or shrinkage cracks.

Ideal for 5-50 mm gap.

PRODUCT INFORMATION

Chemical structure : Cement Based
Appearance/Color : Powder/Gray

USAGE AREAS

Cracks, gaps, holes, etc. that appear when the floor is mopped before floor covering and waterproofing works. to fill problem areas. It is used in repairs before final coat painting, in reinforced and unreinforced concrete repair of columns and beams before ceramic and granite coating, and in chamfering for filling cracks on surfaces such as stairs, walls, aerated concrete and brick. It is suitable for filling gaps up to 5-50 mm.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

503 PROREPAIR SPEED



Fast Drying High Strength Repair and Filling Mortar

APPLICATION EQUIPMENT

Hand mixer - Spatula - Steel Trowel

APPLICATION INSTRUCTIONS

Surface; It must be dry, sound and free of dust. It should be cleaned of any residues such as oil, grease, dirt, paint, salt vomit that would prevent adhesion. Fine cracks should be widened with the help of hilti.

Slowly pour 25 kg of PROREPAIR SPEED into 5-6 liters of water and mix with a low-speed mixer until there are no lumps left. Since it dries quickly, it is recommended to mix the product in small quantities as needed. If a more durable product is desired, PROLATEX can be added to the mortar.

Mortar should be applied by applying pressure with a steel trowel. If more than one coat is to be applied, wait at least 1 hour between coats. This period may be shortened in the summer months. If going to the second floor, the surface must be moistened with a sponge. The prepared mortar should be consumed within 20 minutes, and expired mortar should be disposed of.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. Application should not be made on surfaces at risk of frost. The product should be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

1.3 -1.7 kg/m² for 1 mm thickness

Max 5-50 mm thickness can be applied.

For higher thickness, it is recommended to apply a second coat.

PACKAGING

In 5 kg pp bag,

In a 25 kg kraft bag, (64 pieces on a pallet, 1600 kg)

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +35 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +35 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

503 PROREPAIR SPEED



**Fast Drying High Strength Repair
and Filling Mortar**

SAFETY

Since it is cement based, do not breathe the dust, use a mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test the suitability of the product before using it.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com