

595 PROK M



Cement Based Tile and Ridge Mortar

PRODUCT DESCRIPTION

It is a cement-based, powder polymer-reinforced adhesive mortar used for bonding and fixing roof ridge tiles.

FEATURES

It has high performance and stability.

It is easy to prepare and apply.

It does not sag on horizontal and vertical surfaces.

It is produced in brick and anthracite colours. It is used for adhesion of tiles and ridges in these colors.

PRODUCT INFORMATION

Chemical structure : Cement Based

Appearance/Color : Dust / Brick Color

PERFORMANCE

(23°C, 50% Relative Humidity)

Void Unit Volume Mass of Fresh Mortar 1350 ± 200 kg/m³ TS EN 1015-6

Grain Size Distribution

Amount remaining on the sieve with 1 mm opening %1,0 TS EN 1015-1

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. The values may change as the temperature and humidity values in the construction site environment and the application surfaces and areas will vary.

USAGE AREAS

Ridges and tiles etc. on roofs. It is used for adhesion and assembly of surfaces.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

595 PROK M



Cement Based Tile and Ridge Mortar

APPLICATION EQUIPMENT

Hand mixer - Trowel

APPLICATION INSTRUCTIONS

Surface; It must be dry, sound and free of dust. It should be cleaned of any residues such as oil, grease, dirt, paint, salt vomit that would prevent adhesion. Absorbent and porous surfaces should be moistened with water before application.

Slowly pour 25 kg of PROK M into 5-6 liters of water and mix with a low-speed mixer until no lumps remain. The mortar is left to rest for 5-6 minutes to mature. It is mixed again before application.

The adhesive mortar is spread on the application surface. It is applied to the joints leaving no gaps. The prepared mortar should be consumed within 2 hours.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product should be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

0.60 -0.75 kg / piece

PACKAGING

In a 25 kg kraft bag, (64 pieces on a pallet, 1600 kg)

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +35 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +35 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

595 PROK M



Cement Based Tile and Ridge Mortar

SAFETY

Since it is cement based, do not breathe the dust, use a mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test the suitability of the product before using it.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com