

1002 PROALL EXT



Ready to Use Exterior Putty Plaster

PRODUCT DESCRIPTION

It is a water-based, acrylic emulsion-based, ready-to-use exterior putty product used for repair and filling purposes.

FEATURES

It provides an easy and fast application.

It is suitable for external conditions.

Creates a smooth surface ready for painting.

It penetrates well into the surfaces it is applied to, adheres to the surface very well, is easy to apply, and is matte. It is environmentally friendly.

PRODUCT INFORMATION

Chemical structure : Acrylic Based / Water based

Appearance/Color : Liquid/Cream

PERFORMANCE

(23°C, 50% Relative Humidity)

Intensity 1,80 ±0,2 gr/ cm³

Ph 8 ± 1

Application thickness max.2mm

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. The values may change as the temperature and humidity values in the construction site environment and the application surfaces and areas will vary.

USAGE AREAS

Plaster, concrete, etc. in outdoor areas. It is used in the repair of boards and plastering works before painting.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

1002 PROALL EXT



**Ready to Use
Exterior Putty Plaster**

APPLICATION INSTRUCTIONS

Surface; It must be cured, dry and sound. It should be cleaned of any residues such as oil, grease, dirt, paint, salt vomit that would prevent adhesion.

It is ready for use.

It is first mixed in its own packaging using a low speed mixer. It is applied in two layers with a spatula or trowel to obtain a smooth surface. Before applying the second coat, the first coat must be completely dried.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should not be made in very high temperatures, direct exposure to sunlight, very windy or rainy weather. Application should not be made on surfaces at risk of frost. Application should be made between +5 C and +30 C. Application should never be made at temperatures below 5 C. The product should be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

0.65 - 1.25 kg/m² in a single coat.

PACKAGING

28kg plastic bucket
5kg plastic bucket

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

1002 PROALL EXT



**Ready to Use
Exterior Putty Plaster**

SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, rinse with plenty of water and consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test the suitability of the product before using it.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com