

1006 PROLINE



Ready Dry Screed

PRODUCT DESCRIPTION

It is a factory-mixed, ready-made dry screed mortar that is cement-based, contains polymer additives, is fiber reinforced, and has the strength of screed poured in a construction site environment.

FEATURES

Easy to apply, mixed with water and poured. It saves time and labor. It prevents the formation of cracks thanks to the additives it contains. Thanks to its homogeneous mixture, it provides the same and high strength at every point of application. Since it is a ready-made mixture, material wastage is minimal.

PRODUCT INFORMATION

Chemical Structure : Cement Based

Appearance / Color : Powder / Gray

USAGE AREAS

Indoors and outdoors,
Correcting ground irregularities and eliminating elevation differences,
In places where a smooth, polished finish is desired,
On door and window lintels, beams and lintels, Used in floor coverings and many areas.

APPLICATION INSTRUCTIONS

Surface; It must be cured, dry and sound. It should be cleaned of any residues such as oil, grease, dirt, paint, salt vomit that would prevent adhesion. The surface must be roughened. Broken and hollow areas on the surface should be repaired with PROREPAIR repair mortar at least 24 hours in advance. Areas with high absorbency must be primed with PROGEN primer. The final stage before application should be a dust-free surface.

If the ground is water absorbent, the application should be made by moistening it. The prepared mortar is poured onto the surface, starting from a corner, and the thickness of the mortar should be adjusted with a steel trowel and a gauge. It can be applied in 2-10 cm thickness. If coating is to be done on it, it can be done after 24 hours. It is recommended to complete the process within 15-20 minutes. Expired mortar should be disposed of.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

1006 PROLINE



Ready Dry Screed

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product should be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

Approx. 18 kg/m² (for 1 cm layer thickness)

PACKAGING

In a 25 kg kraft bag, (64 pieces on a pallet, 1600 kg)

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

1006 PROLINE



Ready Dry Screed

SAFETY

Since it is cement based, do not breathe the dust and do not contact it with skin or eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test the suitability of the product before using it.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com