

Paraffin Based Solvent Based Concrete Curing Material

PRODUCT DESCRIPTION

It is a concrete curing material used on paraffin-based concrete, screed and cement-based surfaces, preventing shrinkage cracks that may occur in concrete, protecting fresh concrete against water loss, and creating a mechanical resistance-increasing layer on the surface.

FEATURES

Concrete curing application is an extremely important issue in terms of the durability of concrete. It prevents shrinkage cracks and dust formation in concrete. It protects fresh concrete against water loss by breathing into the pores on the surface. It prevents the concrete from drying quickly and cracking. It reduces the absorption of water. It prevents dust formation.

PRODUCT INFORMATION

Chemical Structure : Paraffin
Appearance/Color : Liquid/Transparent

PERFORMANCE

(23°C, 50% Relative Humidity)

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. The values may change as the temperature and humidity values in the construction site environment and the application surfaces and areas will vary.

USAGE AREAS

Reducing the absorbency of surfaces such as plaster, concrete, plaster, screed, etc.

It is used to prevent sudden water losses in concrete.

It is used to prevent sudden and rapid drying on surfaces where cement-based PROAGREGA Surface Hardener has been applied.

It is applied on screeds, airports, concrete channels, and field concretes that have completed their cure. It is used in concrete casting in places where humidity is low and evaporation and air currents are high.

575 PROCURE P



Paraffin Based Solvent Based Concrete Curing Material

APPLICATION EQUIPMENT

Roller & Airless Spray

APPLICATION INSTRUCTIONS

It is applied without waiting after the concrete loses its free surface water. It dries in 1-2 hours at 20 degrees. Ready for use.

PROCURE P should be shaken before use. The product should be applied homogeneously to the floor with a roller, brush or spraying equipment. Ponding should not be caused. No contribution should be included. A single layer applicable .

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product must be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

150-250 g/m² depending on the absorbency of the surface

PACKAGING

20 kg tin

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

575 PROCURE P



Paraffin Based Solvent Based Concrete Curing Material

SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, rinse with plenty of water and consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products, and it is a recommendation and this information is about the correct application ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com