

585 PRODECO POWDER



Stamped Concrete Mold Releaser Decorative Powder Product

PRODUCT DESCRIPTION

It is a ready-to-use powder mold release product that prevents the mold from sticking and gives an antique color during the patterning process applied after stamped concrete.

FEATURES

- It prevents the molds from sticking.
- It is hydrophobic.
- Creates decorative secondary color.
- Unlimited designs can be made with different molds.
- An extremely decorative and natural appearance is achieved.
- Provides secondary color options.
- It has a natural decorative appearance.
- Provides a smooth and homogeneous appearance.
- It is easy and practical to apply.
- It is easy and fast to prepare.

PRODUCT INFORMATION

Chemical structure	:	Contains stearate
Appearance	:	Powder
Colour	:	Optional

USAGE AREAS

- It is used to prevent stamped concrete molds from sticking to the concrete and to give the floor an antique appearance.
- In steel moulds,
- In plastic molds,
- It can be used in wooden molds.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

585 PRODECO POWDER



Stamped Concrete Mold Releaser Decorative Powder Product

APPLICATION INSTRUCTIONS

Molds must be dry and clean. If there is any dirt remaining from previous uses, it should be cleaned before application.

It is ready for use. It is applied by sprinkling directly.

The application begins after the surface hardener is applied and the polishing process is completed.

When the PRODECO applied surface is not fully hardened, mold release agent is sprinkled on the surface to form a thin layer and the printing process is started with molds. After the printing process, the molds are removed from the surface and washed. When the surface dries, the surface is washed with pressurized water within 1-2 days until the desired effect is achieved.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost.

CONSUMPTION

200-400 gr/m² depending on the type of mold and surface

PACKAGING

10 kg plastic bucket

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

585 PRODECO POWDER



Stamped Concrete Mold Releaser Decorative Powder Product

SAFETY

Do not inhale, avoid contact with skin and eyes. Use protective gloves, glasses, mask and clothing. In case of eye contact, consult a doctor. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products, and it is a recommendation and this information is about the correct application ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com