

662 PRONON MMA



Resin Based Anti-Slip Rough Stair and Floor Paint

PRODUCT DESCRIPTION

It is a thermoplastic resin-based, high-strength paint that creates a non-slip, rough structure on the ground for pedestrian traffic thanks to the aggregates it contains .

FEATURES

It is long lasting.

It adheres maximumly to the surface it is applied to.

It dries quickly.

The ground can be opened to pedestrian and/or vehicle traffic 1-2 hours after application.

It is not affected by UV rays and other atmospheric conditions.

It is not affected by impacts and abrasions caused by pedestrian and vehicle traffic.

It is resistant to abrasion caused by stackers such as forklifts and pallet trucks.

It is not affected by chemicals, exhaust and oil.

It has the ability to stretch thermoplastic, which allows it to work together with the lower surface.

PRODUCT INFORMATION

Chemical Structure : Thermoplastic resin based

Appearance / Color : Liquid / Contact us

PERFORMANCE

(23°C, 50% Relative Humidity)

Intensity 1,30 ±0,2 gr / cm³

Pot Life 15 Min.

Usage Receiving Time 1 Hr

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. Values may change as temperature and humidity values in the construction site environment and application surfaces and areas will vary.

USAGE AREAS

Asphalt, concrete, helicopter concrete, concrete with surface hardener, mosaic, epoxy, etc. It can be used easily on surfaces.

It is used in Akarya station, shopping malls, schools, workplaces, residences and shopping malls' open and closed car parks, shipping and parking ramps, factory walkways, forklift paths and goods acceptance ramps.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

662 PRONON MMA



Resin Based Anti-Slip Rough Stair and Floor Paint

APPLICATION EQUIPMENT

Hand mixer - Roller - Steel Trowel

APPLICATION INSTRUCTIONS:

Surfaces must be clean, smooth, solid, and free from all kinds of dust, oil, dirt, rust, mold oil, detergent, etc., and similar substances and wastes that prevent adhesion. There should be no puddles, moisture or dampness on the concrete floor. It must be a dry ground and the concrete surface humidity must be below 4%. It should be prepared by cleaning with appropriate mechanical surface preparation techniques such as high pressure water jet, vacuum, roughening, sandblasting.

It is mixed in a clean container, free of any substances that prevent adhesion, or in its own packaging, with a low-speed mixer until a homogeneous mixture without lumps is obtained.

It is very important to repair and clean the floor before starting the application. The cracks, gaps and damaged areas on the floor are filled with our very fast-drying repair mortar PROREPAIR MMA and repaired; Before applying anti-slip paint, a smooth and solid surface must be obtained. PROMET 521 primer application is recommended on non-absorbent surfaces. The aggregates it contains may have settled at the bottom of the bucket, the bottom area of the bucket should be mixed thoroughly.

Application is made by spreading it onto the ground using a roller or steel trowel.

The aggregates contained in PRONON MMA Floor Anti-Slip Paint are sufficient for non-slip properties. Exercise should not be done in very cold or very hot weather, under extreme sun or in extremely windy weather.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should not be made in very high temperatures, direct exposure to sunlight, very windy or rainy weather. Application should not be made on surfaces that are at risk of frost at the time of application. Application should be made between +5 C and +30 C. Application should never be made at temperatures below 5 C. After application, it should be protected from rain, water, frost and negative external factors for 24 hours.

CONSUMPTION

0,300 - 0,400 gr/m²

PACKAGING

10 kg tin packaging

3 kg tin packaging



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

662 PRONON MMA



Resin Based Anti-Slip Rough Stair and Floor Paint

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 °C and +25 °C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 °C and +25 °C). It should not be left under direct sunlight.

SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses, mask and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. Avoid skin contact. For detailed information and recommendations, please refer to the Safety Data Sheet .

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com