

Marking and Floor Paint

PRODUCT DESCRIPTION

It is a high-strength, long-lasting MMA-based marking and floor coloring paint mixed with hardener and applied in interior and exterior spaces.

FEATURES

It is produced in traffic paint colors that comply with RAL standards.

It dries very quickly. (On average within 1 hour)

It is very resistant to UV rays and other atmospheric conditions.

It is very easy to use.

It is not affected by dirt, dust, exhaust and oil.

It has the ability to stretch thermoplastic, which allows it to work together with the lower surface.

It is not necessary to remove old paint from the surface when it needs to be renewed.

PRODUCT INFORMATION

Chemical Structure : Methyl Methacrylate Based

Appearance / Color : Liquid / Contact us.

PERFORMANCE

(23°C, 50% Relative Humidity)

Intensity 1,50±0,2 kg/lt

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. Values may change as temperature and humidity values in the construction site environment and application surfaces and areas will vary.

USAGE AREAS

Asphalt, concrete, surface hardener, mosaic, etc. It can be used easily on surfaces. It is also ideal for painting paving curb stones.

It can be used on non-absorbent surfaces such as metal and marble by applying Promet 521 Primer.

Lines, arrows, pedestrian crossings, letters and numbers can be applied easily.

Main areas of use:

Warehouse, factory, parking lot, all kinds of military areas,

Airports, ports, shipyards,

All kinds of industrial areas, workshops and warehouses,

Inner and outer city roads, bridges, viaducts, pedestrian paths, landscaping, health facilities, hospitals, shopping malls, business centers, hotels, holiday villages.

810 PROFLOOR 2K



Marking and Floor Paint

APPLIACATION EQUIPMENT

Hand mixer - Trowel - Roller - Brush

Since the product has the application viscosity, there is no need for dilution.

APPLICATION INSTRUCTIONS

The surface to be applied must be dry, dust-free, free of oil and other dirt. The surface temperature of the road must be above 5 °C. It is recommended to clean the old paint on the floor. However, if the old paint on the surface cannot be cleaned easily, it can be applied over it. If application will be made in a closed area, the ventilation in the environment should be good. The second component, the powder hardener, should be added and mixed homogeneously for approximately 1 minute with a low-speed mixer in the bucket, and should be poured onto the application area without waiting. It is spread appropriately with a roller or trowel. Optionally, a single or double layer can be applied to the floor. Application should not be made under direct sunlight in very hot weather. The product dries quickly, so you have a maximum of 20-30 minutes to apply it. If you exceed this range, the product may become unusable as it will harden.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product should be protected from rain, water, frost and negative external factors until it is cured. Ask for technical support for ground conditions before application.

CONSUMPTION

Approximately 500 -800 gr/m² depending on the ground

PACKAGING

5 kg tin packaging

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +10 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging, in a dry and cool, moisture-free environment (temperature between +10 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

810 PROFLOOR 2K



Marking and Floor Paint

SAFETY

Do not breathe the product, use a mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com