

Polished Concrete Floor Polish

PRODUCT DESCRIPTION

It is a single-component, air-drying floor polish that can be applied indoors and outdoors on mineral floor and wall surfaces, forming a very bright and very thin film layer.

FEATURES

It protects the floor and prevents dust formation.

It has an effective impregnation and a quick drying time (approximately 1 hour).

It is very long lasting.

It is very easy to apply and non-toxic.

Since it penetrates into the pores of the surface, it prevents dust from forming inside the surface. It improves the appearance quality of the surface on which it is applied.

It allows vibrant colors to appear and motifs to stand out.

It protects the applied surface against climatic conditions such as UV rays, rain and snow, and allows the surface to breathe.

PRODUCT INFORMATION

Shape: Liquid

Color: Transparent

PERFORMANCE

(23°C, 50% Relative Humidity)

Intensity 1,30 ±0,2 gr / cm³

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. Values may change as temperature and humidity values in the construction site environment and application surfaces and areas will vary.

USAGE AREAS

Vertically and horizontally on concrete, exposed concrete, brick, natural stone, mosaic and many mineral surfaces, On concrete, screed and paving stones,

Internal and external applications,

Warehouses and factories, fuel stations,

Shopping malls, supermarkets,

It can be applied on warehouse floors.

816 PROPERA



Polished Concrete Floor Polish

APPLICATION EQUIPMENT

Hand Mixer & Roller & Spray Equipment

APPLICATION INSTRUCTIONS

Surfaces must be clean, smooth, solid, and free from all kinds of dust, oil, dirt, rust, mold oil, detergent, etc., and similar substances and wastes that prevent adhesion. There should be no puddles, moisture or dampness on the concrete floor. It should be a dry ground. The floor must be free of any substances that prevent adhesion. PROPERA 816 is mixed in its own packaging with a low-speed mixer for about 1 minute and applied to the floor in 2 layers with a roller, brush or spraying equipment. It dries quickly, 1 hour between coats is sufficient.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should not be made in very high temperatures, direct exposure to sunlight, very windy or rainy weather. Application should not be made on surfaces that are at risk of frost at the time of application. Application should be made between +5 C and +30 C. Application should never be made at temperatures below 5 C. After application, it should be protected from rain, water, frost and negative external factors for 24 hours.

CONSUMPTION

100 gr/m²

PACKAGING

5 kg tin packaging

15 kg tin packaging

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

816 PROPERA



Polished Concrete Floor Polish

SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses, mask and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. Avoid skin contact. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com