

824 PROFLOOR X SHINE



Hybrid Resin Based Two Component Solvent Glossy Floor Paint

PRODUCT DESCRIPTION

It is a two-component, solvent-based topcoat paint that is resistant to standard usage conditions and chemicals, consists of a range of different resins, and can be applied to concrete, metal, wood, plaster and plaster surfaces.

FEATURES

- It has solvent.
- It is water impermeable.
- It is resistant to chemicals and bacteria.
- It is resistant to freezing.
- It is long-lasting and its color does not fade.
- It is hygienic and can be cleaned.

PRODUCT INFORMATION

- Chemical Structure : Hybrid Mixture
Color / Appearance : RAL Chart / Liquid
Mixing Ratio : A / B: 1 6/4 by mass

PERFORMANCE

(23°C, 50% Relative Humidity)

| | |
|---|--------------------------------|
| Mixture Density | 1,50 ± 0,05 gr/cm ³ |
| Pot life | ~60 Min (20°C) |
| Walkable Time | 1 day Full Strength 7 days |
| Temperature Resistance | (-20°C)-(+60°C) |
| Adhesion Strength to Substrate: 28 days | 2 N/mm TS EN 1348 |

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. Values may change as temperature and humidity values in the construction site environment and application surfaces and areas will vary.

USAGE AREAS

- Indoors and outdoors, on concrete and metal surfaces,
- In areas where chemicals are used,
- On tiles, ceramics, granite ceramics, mosaics, glass mosaics and porcelain mosaics (by sanding the glaze on it)
- Suitable for walls, ceilings and floors.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

824 PROFLOOR X SHINE



Hybrid Resin Based Two Component Solvent Glossy Floor Paint

APPLICATION EQUIPMENT

Mixer, Roller, Brush, Spraying Equipment .

APPLICATION INSTRUCTIONS

Surface Quality: The surfaces to be applied must be solid, clean, dry and free of all foreign substances that may cause separation.

Surface Preparation: If there are any cracks or breaks on the surface, they should be repaired with PROREPAIR or our epoxy repair mortars at least 24 hours in advance. Before applying the floor, a suitable primer should be primed with or without solvent. The surface must be smooth and solid as the roughnesses on the surface will be reflected exactly on the paint. Mixing: it is a two-component product. Component B is added into component A and mixed with a slow-speed drill until a homogeneous mixture is obtained.

- While mixing and applying, use rubber gloves and goggles to protect your skin and eyes from being affected. The eyes should be especially carefully protected. If it gets into your eyes, rinse with plenty of water for about 15 minutes and consult a physician immediately.

- Keep away from foodstuffs and children.

- The second coat of paint should be applied within at least 12 and at most 36 hours.

- It reaches full strength after 7 days. Surface; It must be cured, dry and sound. It should be cleaned of any residue such as oil, grease, dirt, paint, salt vomit that would prevent adhesion.

For metal surfaces, if there is any dirt on them, they can be cleaned and sandblasted to create a rough surface.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should not be made in very high temperatures, direct exposure to sunlight, very windy or rainy weather. Application should not be made on surfaces that are at risk of frost at the time of application. The applied area should not be exposed to traffic until full cure is achieved. Application should be made between +5 C and +25 C. Application should not be made at temperatures below C.

CONSUMPTION

200-300 gr/m² depending on the absorbency of the surface .

PACKAGING

A Bile en 16 kg te neke a mbalaj

B Bile en 4 kg teneke ambalaj

Total 20 kg set

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

824 PROFLOOR X SHINE



Hybrid Resin Based Two Component Solvent Glossy Floor Paint

SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses, mask and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. Avoid skin contact. Do not swallow. Keep away from flame sources. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com