

# 825 PROFLOOR X



## **Hybrid Resin Based General Floor Paint**

### **PRODUCT DESCRIPTION**

It is a hybrid structure, solvent-based, UV-resistant floor paint produced with a mixture of different thermoplastic resins.

### **FEATURES**

- It is suitable for use indoors and outdoors.
- It is produced in all RAL codes.
- It is very easy to apply and does not require any extra expertise.
- It does not create labor costs.
- It contributes to waterproofing and is waterproof.
- It has high covering power.
- It is resistant to snow, rain, sun and water.
- It is applied quickly and easily.
- It is resistant to heavy loads such as trucks, forklifts and pallet trucks.
- It does not yellow or fade over time.
- It is resistant to abrasion.
- It is not affected by pedestrian traffic.
- It can be used on vertical and horizontal surfaces such as walls and ceilings.
- It covers the surface perfectly homogeneously.
- It prevents dust formation.

### **PRODUCT INFORMATION**

- Chemical structure : Thermoplastic Acrylate Hybrid Based / Solvent based
- Appearance/Color : Liquid / Contact us
- Intensity : 1,30 ±0,2 gr / cm<sup>3</sup>

### **PERFORMANCE**

(23°C, 50% Relative Humidity)

Intensity 1,30 ±0,2 g / cm<sup>3</sup>

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. Values may change as temperature and humidity values in the construction site environment and application surfaces and areas will vary.

### **USAGE AREAS**

- In concrete, screed and paving stones,
- Internal and external applications,
- Warehouses and factories, fuel stations
- Shopping malls, supermarkets,
- On warehouse floors,
- Touristic facilities, bicycle paths, coastline, walking paths, squares, parks and gardens.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti  
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78  
Gürsu /BURSA TÜRKİYE  
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01  
www.barskimya.com info@barskimya.com

# 825 PROFLOOR X



## *Hybrid Resin Based General Floor Paint*

### **APPLICATION EQUIPMENT**

Hand mixer - Can be applied with roller or spray equipment.

### **APPLICATION INSTRUCTIONS**

Surface; It must be cured, dry and sound. It should be removed from residues such as oil, grease, dirt and dust that would prevent adhesion.

PROFLOOR x 825 FLOOR PAINT; In its application, ground structure is very important. Before painting, damaged floors are filled with one of our PROREPAIR MMA repair mortars and repaired. Cleanliness on the floor is very important. If there are areas with oil residue, they should be cleaned with cellulosic thinner. It should not be applied to wet and damp surfaces. This may cause blistering. Additionally, floor paint should not be applied thickly. If applied thickly, the paint cannot remove the gas in the air and may create air bubbles. It is recommended to apply PROMET 521 primer before painting. The product is ready for use. 400 rpm until the product reaches a homogeneous consistency. It should be mixed with a rotating mixer until it becomes homogeneous. It is applied directly in two layers. It dries quickly, in about 1-2 hours. You should wait at least 1 hour between coats.

### **LIMITATIONS**

To obtain optimum quality, please adhere to the application instructions. Application should not be made in very high temperatures, direct exposure to sunlight, very windy or rainy weather. Application should not be made on surfaces that are at risk of frost at the time of application. Application should be made between +5 C and +30 C. Application should never be made at temperatures below 5 C. After application, it should be protected from rain, water, frost and negative external factors for 24 hours.

### **CONSUMPTION**

200-300 gr/m<sup>2</sup>

### **PACKAGING**

9 kg tin packaging  
18 kg tin packaging

### **SHELF LIFE**

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

### **STORAGE CONDITIONS**

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti  
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78  
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01  
www.barskimya.com info@barskimya.com

# 825 PROFLOOR X



**Hybrid Resin Based  
General Floor Paint**

## SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses, mask and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. Avoid skin contact. For detailed information and recommendations, please refer to the Safety Data Sheet.

## LEGAL NOTES

*Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.*

*DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.*

*DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.*



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti  
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78  
Gürsu /BURSA TÜRKİYE  
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01  
www.barskimya.com info@barskimya.com