

# 847 PROFLOOR BOND



## *Water Based Acrylic Based PVC And Carpet Adhesive Glue*

### PRODUCT DESCRIPTION

It is a water-based, acrylic resin-based, general-purpose PVC, carpet and linoleum adhesive containing adhesion-enhancing fillers and additives.

### FEATURES

It does not contain solvents. Since it is water-based, it can be used safely indoors. It spreads easily and is easy to apply. It has a long working time. It has the flexibility and adhesion ability to allow errors that occur when placing the coating to be corrected. In addition to cement-based leveling screeds, it can also be applied on gypsum-based leveling screeds. It has high adherence to the ground. Provides high adhesion strength. Suitable for floors with underfloor heating. It is resistant to wheeled items. It is economical.

### PRODUCT INFORMATION

It is an acrylic-based, solvent-free, single-component, general-purpose dispersion floor covering adhesive that provides fast and strong adhesion, used especially for adhering PVC and linoleum floor coverings to pre-leveled surfaces.

### USAGE AREAS

It is used for bonding homogeneous and heterogeneous PVC floor coverings, linoleum-based floor coverings, rubber-based roll coverings in indoor and dry environments, horizontal floors, residences, hospitals, educational buildings, shopping malls, stores and markets.

### TECHNICAL SPECIFICATIONS

Intensity ~ 1,35 ± 0,05 kg/ltr

Waxing Time 25 - 35 Min

Open Working Time 35 - 45 minutes

Opening Time to Traffic 24 - 48 hours

Full Curing 3 - 4 days

Application Temperature Between +15°C and +30°C

Service Temperature Between +5°C / +70°C



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti  
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78  
Gürsu /BURSA TÜRKİYE  
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01  
www.barskimya.com info@barskimya.com

# 847 PROFLOOR BOND



***Water Based Acrylic Based  
PVC And Carpet Adhesive Glue***

## **APPLICATION INSTRUCTIONS**

The ground must be flat, dry and crack-free. The surface is free of dust, dirt, oil, etc. that will prevent adhesion. must be cleared of contaminants. In order to obtain smooth surfaces, the material must be used in accordance with its technical specifications.

It can be applied with A1, A2 and B1 toothed trowel bits. Tools can be cleaned with water immediately after application. The product should be mixed thoroughly in its packaging before use. The maximum open working time is 35 - 45 minutes. The creamy layer that will form on the top of the package during long waiting should be removed. It should be spread homogeneously on the ground with a notched trowel suitable for the characteristics of the ground to be applied. On the adhesive spread on the floor 10 ndash; After 15 minutes the flooring can be glued. Welding can only be done 24 hours after the application time. In underfloor heating systems, it should be turned on 10 days before application and turned off during coating. Heating can be turned on again 72 hours after application.

## **CONSUMPTION**

250- 450 g/m<sup>2</sup> (It may vary depending on the type of comb used, application thickness, absorbency and smoothness of the floor, type of coating material and environmental conditions).

## **PACKAGING**

20 kg plastic bucket

## **SHELF LIFE**

It is valid for 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The packaging should be tightly closed when not in use. It should be kept away from moisture.

## **STORAGE CONDITIONS**

Since it is in meltable bags, contact with water and moisture should be prevented. It should be stored in its unopened original packaging, in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left directly outdoors under rain, snow and sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti  
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78  
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01  
www.barskimya.com info@barskimya.com

# 847 PROFLOOR BOND



**Water Based Acrylic Based  
PVC And Carpet Adhesive Glue**

## SAFETY

Since it is cement based, do not breathe the dust, use a mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

## LEGAL NOTES

*Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.*

*DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.*

*DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.*



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti  
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78  
Gürsu /BURSA TÜRKİYE  
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01  
www.barskimya.com info@barskimya.com