

Anti-Dusting for Concrete Surfaces

PRODUCT DESCRIPTION

It is a resin-based, solvent-based, low-viscosity floor polish that penetrates deeply into the pores of mineral-based surfaces, prevents dust formation, reduces water permeability and gives shine.

FEATURES

Single component. It is based on riding.

It is easy to use.

Ready to use.

It prevents dust formation.

It has high adherence.

It can be deleted. It does not retain dirt.

It creates a shiny film. It dries quickly.

PRODUCT INFORMATION

Chemical Structure : Resin based / Solvent based

Appearance / Color : Liquid / Almost transparent

USAGE AREAS

It is applied after cement-based floor coatings.

On cement floors in commercial and private residences.

In open and closed areas, factories, warehouses, parks, car parks, car repair shops, on the floors of train stations and logistics centres.

It is applied on the floors of show halls, restaurants, event and congress centers or museums.

Anti-Dusting for Concrete Surfaces

APPLICATION EQUIPMENT

Hand mixer, Roller, Airbrush

APPLICATION INSTRUCTIONS

Surface; It must be cured and solid. The surface is strengthened by removing residues such as loose surface, mortar and concrete pieces. It should be cleaned from residues such as oil, grease, dirt, paint and salt vomit that will prevent adhesion. The floor should not be wet and damp.

PROTEC is ready for use. The product is mixed at 400-600 rpm with the help of a medium speed mixer. It is mixed quickly until it becomes a homogeneous mixture. It is applied with a roller and air gun. It is recommended to apply thinly to the floor in 2 coats.

The first layer strengthens the floor by filling the pores. The second layer is applied after 2 hours. The second coat increases scratch and abrasion resistance. It creates a homogeneous, shiny surface on the floor. Thick application should be avoided.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product should be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

Approximately 100 gr / m²

PACKAGING

5 kg tin packaging

15 kg tin packaging

SHELF LIFE

It is 1 year from the date of production in its original packaging with the lid closed, in a dry and moisture-free environment, away from direct sunlight, at a temperature of +5 - 25 C and 50% relative humidity. The lids of the packages should be closed tightly when not in use. It should be kept away from moisture. Protect from high temperatures and frost.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a dry and cool (temperature between +5 C and +25 C) environment free of moisture. It should not be left under direct sunlight.

Anti-Dusting for Concrete Surfaces

SAFETY

Do not inhale, use mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.