

730 PROPOWDER



Powder Water Repellent for Mortar & Plaster

PRODUCT DESCRIPTION

It is a silicone-based, stearate-added, white-coloured, powder water-repellent additive that creates a high-quality water-repellent surface.

FEATURES

It provides water impermeability by preventing the formation of capillary cracks and gaps.

It reduces the amount of capillary water absorption of the surface.

Provides crack-free durability.

It increases the resistance of added mortars against capillarity and water absorption under high pressure.

PRODUCT INFORMATION

Chemical structure : Silicone & Stearate

Appearance/Color : Powder/White

USAGE AREAS

It can be used safely in plaster and screed works of all kinds of mineral-based building elements exposed to water and moisture, used in all kinds of plaster, screed and concrete works where water impermeability is required. It is used in under-ceramic screed works on surfaces that are constantly in contact with water, such as bathrooms, kitchens and balconies.

It is used in exterior plasters against moisture caused by rain or washing water.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

730 PROPOWDER



Powder Water Repellent for Mortar & Plaster

APPLICATION INSTRUCTIONS

It is ready for use. It is used directly.

1 - 3% of the dry mortar is added to the mortar mixing water.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product must be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

1-3% of dry mortar

PACKAGING

- 1 kg Plastic Bucket
- 3 kg Plastic Bucket
- 10 kg Plastic bucket

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

730 PROPOWDER



Powder Water Repellent for Mortar & Plaster

SAFETY

Do not breathe the dust and do not contact the skin and eyes. Use mask. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com