

526 PROWOOD PAINT



Wooden Look Exterior Paint

PRODUCT DESCRIPTION

It is a water-based, acrylic emulsion-based, specially developed, flexible and semi-gloss, wood-look exterior paint.

FEATURES

It has high covering power.
It has high adherence.
It is resistant to rain.
It is matte.
It is easy to apply.
It is environmentally friendly.

PRODUCT INFORMATION

Chemical structure : Styrene Acrylic based / Water based
Appearance/Color : Liquid / Brown Yellow
Ph : 7-10
Intensity : 1,30±0,2gr/cm³

PERFORMANCE

(23°C, 50% Relative Humidity)

Brightness G2 TS 4318 EN ISO 2813
Grain Size S1 TS 2620 EN ISO 1524
Water Transfer Rate W2 TS EN 1062-3

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. Values may change as temperature and humidity values in the construction site environment and application surfaces and areas will vary.

USAGE AREAS

It is applied on smooth surfaces on interior and exterior surfaces. If the area to be applied is rough, PROPLASTER 525 plaster is applied and then applied on top.

APPLICATION EQUIPMENT

Hand mixer - Roller - Pattern Attachment



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

Wooden Look Exterior Paint

APPLICATION INSTRUCTIONS

Surface; It must be cured, dry and sound. It should be cleaned of any residue such as oil, grease, dirt, paint, salt vomit that would prevent adhesion. The surface should be rough. If there are significant defects on the application surface, they should be repaired with PROREPAIR THIN at least 24 hours in advance.

PROPLASTER plaster is applied. When drying occurs after 24 hours, PROTHERM PRIMER application is started.

PROTWOOD PAINT Exterior Paint is diluted with 10 - 15% water and mixed with a low speed mixer. 24 hours before, PROTHERM Primer is applied as a thick coat on the surface primed with an exterior primer in a suitable color (primer color is important, some parts of the patterned areas will be visible when the application is completed). A knotted or striped wood pattern is obtained by passing a properly selected pattern horizontally onto the painted surface with the help of a gauge.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product should be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

7-9 m² / lt in a single coat, depending on the absorbency of the surface

PACKAGING

7.5liter plastic bucket

15 liter plastic bucket

SHELF LIFE

It is 1 year from the date of production in its original packaging with the lid closed, in a dry and moisture-free environment, away from direct sunlight, at a temperature of +5 - 25 C and 50% relative humidity. The lids of the packages should be closed tightly when not in use. It should be kept away from moisture. Protect from high temperatures and frost.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.

526 PROWOOD PAINT



Wooden Look Exterior Paint

SAFETY

Do not inhale the product and do not contact it with skin or eyes. Use protective gloves, glasses and clothing. In case of eye contact, rinse with plenty of water and consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products, and it is a recommendation and this information is about correct application ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com