

801 PROWALL



Exterior Crack Concealer Waterproofing Paint

PRODUCT DESCRIPTION

It is a water-based, acrylic emulsion-based, flexible insulation paint consisting of special mineral filler and polymer components, with excellent water resistance and strong adherence ability.

FEATURES

It has high covering power. It has high adherence.

Resistant to rain and frost. It is elastic.

It penetrates well into the surfaces on which it is applied, adheres to the surface very well, and closes the cracks formed on the surface.

It is easy to apply and creates a long-lasting flexible film on surfaces thanks to its high mechanical resistance. It is matte and easy to apply. It is environmentally friendly.

PRODUCT INFORMATION

Chemical Structure :	Acrylic Based / Water based
Appearance / Color :	Liquid / Contact Us
Ph :	7-10
Intensity :	1,40 ±0,2 gr / cm ³

PERFORMANCE

(23°C, 50% Relative Humidity)
(valid for undiluted product)

Maximum Pressure 28 days	15 N
Maximum Stretch 28 days	5 N/mm ²
Adherence (concrete) 28 days	1N/mm ²
Elongation at break 28 days	%600

These values were obtained as a result of laboratory experiments and are valid for the performance of finished applications at the end of the full drying period. Values may change as temperature and humidity values in the construction site environment and application surfaces and areas will vary.

USAGE AREAS

It is also applied as a final coat of paint on the exterior.

APPLICATION EQUIPMENT

Hand Mixer - Roller - Brush



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

801 PROWALL



Exterior Crack Concealer Waterproofing Paint

APPLICATION INSTRUCTIONS

Surface; It must be cured, dry and sound. It should be cleaned of any residue such as oil, grease, dirt, paint, salt vomit that would prevent adhesion. Primer application should be made. Approximately 10% water is added and mixed with a low speed mixer. The surface must be primed before applying paint. After 24 hours of waiting time, the first layer is diluted 10% and applied to the surface with a roller. After 24 hours, the second layer is applied in the same way.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should not be made in very high temperatures, direct exposure to sunlight, very windy or rainy weather. Application should not be made on surfaces at risk of frost. Application should be made between +5 C and +30 C. Application should never be made at temperatures below 5 C. The product should be protected from rain, water, frost and negative external factors until it cures.

CONSUMPTION

300-400 gr / m²

PACKAGING

3kg plastic bucket

5kg plastic bucket

18 kg plastic bucket

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

801 PROWALL



Exterior Crack Concealer Waterproofing Paint

SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, rinse with plenty of water and consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com