

Tile Paint

PRODUCT DESCRIPTION

Thermoplastic resin based, solvent based, single component, fast drying, resistant to all weather conditions; It is a new generation strong tile paint developed for painting red tile, concrete, stone and all mineral-based roofing types.

Tile Paint, sun, snow, rain, etc. It has maximum resistance against the corrosive effects of weather conditions. It dries quickly thanks to its cellulosic chemical components. Its application is very simple. It has a waterproof and flexible structure. It fills and closes the fine cracks in the tiles. It does not create extra labor costs and anyone can easily apply it.

FEATURES

- It is very easy to apply and does not require any extra expertise.
- It contributes to waterproofing and is waterproof.
- It has high covering power.
- It is resistant to snow, rain, sun and water.
- It is applied quickly and easily.
- It does not yellow or fade over time.
- It is resistant to abrasion.
- It is not affected by pedestrian traffic.
- It can be used on vertical and horizontal surfaces such as walls and ceilings.
- It covers the surface perfectly homogeneously.

PRODUCT INFORMATION

- Chemical Structure : Thermoplastic Acrylate Hybrid Based / Solvent based
- Appearance / Color : Liquid / Contact us
- Intensity : 1,30 ±0,2 g / cm³

PERFORMANCE

(23°C, 50% Relative Humidity)

Intensity 1,30 ±0,2 g / cm³

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. Values may vary as temperature and humidity values in the construction site environment and application surfaces and areas will vary .

USAGE AREAS

For all types of tiles with absorbent surfaces.

Tile Paint

APPLICATION EQUIPMENT

It can be applied with hand mixer - Roller - Spray equipment.

APPLICATION INSTRUCTIONS

Surface; It must be cured, dry and sound. It should be removed from residues such as oil, grease, dirt and dust that would prevent adhesion. Before painting the damaged floors, they are filled with our PROREPAIR MMA repair mortar and repaired. Cleaning of the floor is very important. If there are areas with oil residue, they should be cleaned with cellulosic thinner. It should not be applied to wet and damp surfaces. This may cause blistering. Additionally, floor paint should not be applied thickly. If applied thickly, the paint cannot remove the gas in the air and may create air bubbles.

It is ready for use. 400 rpm until the product reaches a homogeneous consistency. It should be mixed with a rotating mixer until it becomes homogeneous. PROMET 521 is applied directly after primer in two layers. Airless spray system is recommended. It dries in about 1 hour.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should not be made in very high temperatures, direct exposure to sunlight, very windy or rainy weather. Application should not be made on surfaces that are at risk of frost at the time of application. Application should be made between +5 C and +30 C. Application should never be made at temperatures below 5 C. After application, it should be protected from rain, water, frost and negative external factors for 24 hours .

CONSUMPTION

250 gr/m²

PACKAGING

10 kg tin packaging

20 kg tin packaging

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.

803 PROKIM



Tile Paint

SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, rinse with plenty of water and consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com