

811 PROBETON ART



Concrete Look Ready Decorative Interior and Exterior Plaster

PRODUCT DESCRIPTION

It is a water-based, acrylic emulsion-based, special mineral filler and polymer components, ready-to-use, paste-like, flexible, concrete-effect decorative plaster with excellent water resistance and strong adherence ability .

FEATURES

It can be used on interior and exterior surfaces.

It has high covering power.

It has high adherence.

It is resistant to rain, frost and sun.

It gives the appearance of exposed concrete.

It is flexible and does not crack.

It penetrates well into the surfaces on which it is applied and adheres very well to the surface.

It closes the cracks formed on the surface.

It is easy to apply and has high mechanical resistance.

It is matte and easy to apply.

It is environmentally friendly.

PRODUCT INFORMATION

Chemical Structure : Acrylic Based / Water based

Appearance / Color : Paste / Gray

USAGE AREAS

It is applied to give a final coat pattern on interior and exterior surfaces of concrete, walls, plasterboard, betopan, ceilings and walls.

APPLICATION EQUIPMENT

Hand Mixer - Trowel - Steel Trowel - Spatula



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

Concrete Look Ready **Decorative Interior and Exterior Plaster**

APPLICATION INSTRUCTIONS

Surface; It must be cured, dry and sound. It should be cleaned of any residue such as oil, grease, dirt, paint, salt vomit that would prevent adhesion. PROGEN Primer application is recommended for used interior surfaces and PROCONTACT PR Primer application is recommended for exterior surfaces. Application Temperature: (+5°C) - (+35°C) .Surface drying approximately 24 hours. Full drying: 2 - 3 days. (Lower temperature and higher relative humidity increase drying time.)The first layer is leveled using the plastering method using a steel trowel and special effect spatulas, and the second layer is applied giving the desired pattern.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should not be made in very high temperatures, direct exposure to sunlight, very windy or rainy weather. Application should not be made on surfaces at risk of frost. Application should be made between +5 C and +30 C. It should never be applied at temperatures below 5 C. The product should be protected from rain, water, frost and negative external factors until it cures.

CONSUMPTION

Approximately 1.5 kg/m² depending on the surface

PACKAGING

5 kg plastic bucket
15 kg plastic bucket

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.

811 PROBETON ART



Concrete Look Ready

Decorative Interior and Exterior Plaster

SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, rinse with plenty of water and consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com