

856 PROVARNISH



Natural Stone Varnish Polish

PRODUCT DESCRIPTION

It is a resin-based, solvent-containing, low-viscosity, mineral-based, water-repellent, anti-dust, shine-giving, protective varnish that can penetrate deeply into the pores of the surface.

FEATURES

- It is single component, kohl based.
- It is waterproof.
- It is easy to use. Ready to use.
- It has high adherence.
- It can be erased. It creates a shiny film.
- It dries quickly.

PRODUCT INFORMATION

- Chemical Structure : Resin Based / Solvent Based
- Appearance / Color : Liquid / Almost transparent

PERFORMANCE

(23°C, 50% Relative Humidity)

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. The values may change as the temperature and humidity values in the construction site environment and the application surfaces and areas will vary.

USAGE AREAS

- All natural artificial stone, brick and cement based absorbent floor coverings.
- On cement-coated floors and walls in commercial and private residences.
- In open and closed areas, on the floors of factories, warehouses, parks, parking lots, car repair shops, train stations and logistics centers.
- It can be used on the floors of performance halls, restaurants, event and convention centers or museums.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

856 PROVARNISH



Natural Stone Varnish Polish

APPLICATION EQUIPMENT

Hand mixer - Roller - Brush - Spraying Equipment

APPLICATION INSTRUCTIONS

Surface; It must be cured and solid. Remains such as loose surface, mortar, concrete pieces are cleaned and the surface is strengthened. It should be cleaned of any residues such as oil, grease, dirt, paint, salt vomit that would prevent adhesion.

It is ready for use. The product is mixed at 400-600 rpm with the help of a medium speed mixer. It is mixed quickly until it becomes a homogeneous mixture. It is applied by roller, brush or spraying. 2 thin coats are recommended. The first layer strengthens the floor by filling the pores. The second coat increases scratch and abrasion resistance. It creates a homogeneous, shiny surface on the floor.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product should be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

Two coats 100 -200 gr/m²

PACKAGING

5 kg tin packaging

15 kg tin packaging

SHELF LIFE

It is 1 year from the date of production in its original packaging with the lid closed, in a dry and moisture-free environment, away from direct sunlight, at a temperature of +5 - 25 C and 50% relative humidity. The lids of the packages should be closed tightly when not in use. It should be kept away from moisture. Protect from high temperatures and frost.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

856 PROVARNISH



Natural Stone Varnish Polish

SAFETY

Do not inhale, use mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com