

Exposed Concrete Primer

PRODUCT DESCRIPTION

It is a water-based, acrylic emulsion-based, exposed concrete surface primer with high scratch resistance and containing special aggregate.

FEATURES

It increases adhesion strength and surface adherence by creating a rough surface for plaster, plaster and plate bonding on smooth exposed concrete floors .

It is ready for use.

It is environmentally friendly.

PRODUCT INFORMATION

Chemical structure : Acrylic based / Water based
Aggregate Structure : Basalt
Appearance/Color : Liquid / Yellow

PERFORMANCE

(23°C, 50% Relative Humidity)

Ph : 7-10
Intensity : 1,40 ±0,2 gr/ cm³
Grain Size : S4 TS 2620 EN ISO 1524

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. Values may change as temperature and humidity values in the construction site environment and application surfaces and areas will vary.

USAGE AREAS

It is used on exposed concrete surfaces such as walls, columns and ceilings.

Exposed Concrete Primer

APPLICATION EQUIPMENT

Hand mixer - Brush - Roller

APPLICATION INSTRUCTIONS

Surface; It must be cured, dry and sound. It should be cleaned of any residue such as oil, grease, dirt, paint, salt vomit that would prevent adhesion. Ready to use. The product is ready for use. 15 kg of PROCONTACT PR is mixed thoroughly with a low-speed mixer and then applied with a brush or roller. It is recommended to mix with a low speed mixer at less than 500 rpm. Due to its aggregate content, the material in the container should be mixed periodically throughout the application. It should not be applied before it dries. The temperature of the application surface should be 5°C-30°C and the surface should not receive precipitation. After drying, application should be started at least 24 hours later.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product should be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

0.300 kg/m² depending on the absorbency of the surface

AMBALAJ

15 kg Plastic Bucket Plastic Bucket

SHELF LIFE

It is 1 year from the date of production in its original packaging with the lid closed, in a dry and moisture-free environment without direct sunlight (temperature between +5 C and +25 C), at a temperature of +5-30 C and 50% relative humidity.

The lids of the packages should be closed tightly when not in use. It should be kept away from moisture. Protect from high temperatures and frost.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.

865 PROCONTACT PR



Exposed Concrete Primer

SAFETY

Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, rinse with plenty of water and consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products, and it is a recommendation and this information is about correct application ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE

Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com