

Grass Paint

PRODUCT DESCRIPTION

It is a water-based acrylic emulsion-based, organic grass coloring paint that turns yellowed, dried grass, plants and soil areas into a natural green color. It is a fast and ideal solution for countryside wedding areas and unturfed areas that need to be opened quickly.

FEATURES

It is an organic grass coloring dye that dyes plants a natural green color. It can be produced in desired shades of green as well as colors such as red and yellow. BARS grass paint is also used to give natural green color in sand and soil areas. It spreads easily on lawn surfaces. It has high adhesion strength and dries quickly within 2-3 hours. Grass areas are lush green in all seasons and in all climatic conditions, and are not affected by the irrigation regime of the grass area and rain. It does not harm the grass and the environment because it does not contain harmful chemicals, heavy metals and other fillers. BARS grass paint is completely water-based and environmentally friendly. It does not contain VOCs and is extremely simple to apply.

Single component. It is easy to use. Ready to use.

It has high adherence.

It minimizes repair costs.

PRODUCT INFORMATION

Chemical Structure : Water based

Appearance / Color : Liquid / Green

PERFORMANCE

(23°C, 50% Relative Humidity)

Drying time 300 min

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. The values may change as the temperature and humidity values in the environment and the application surfaces and areas will vary.

USAGE AREAS

It is used in completely yellowed and dried grass areas, yellowed grass in countryside wedding halls, site gardens, soil areas where grass does not grow for opening purposes, dried plants, sandy areas and football fields .

Grass Paint

APPLICATION INSTRUCTIONS

Before starting the application, the grass area is mowed to a height of 2 cm. In this way, the grass leaves remain upright and BARS grass dye can reach all the yellowed and dried areas underneath. The grass area is raked with a suitable rake, without damaging the grass leaves, and foreign materials and dead plant materials are removed from the area.

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product should be protected from rain, water, frost and negative external factors until it is cured.

CONSUMPTION

An area of 10-15 m² can be painted with 1 kg of grass paint.

PACKAGING

1kg plastic bottle
10 kg plastic drum

SHELF LIFE

It is 1 year from the date of production in its original packaging with the lid closed, in a dry and moisture-free environment without direct sunlight, at a temperature of +5 - 25 C and 50% relative humidity. The lids of the packages should be closed tightly when not in use. It should be kept away from moisture. Protect from high temperatures and frost.

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a dry and cool (temperature between +5 C and +25 C) environment free of moisture. It should not be left under direct sunlight.

884 PROGRAS PAINT



Grass Paint

SAFETY

Do not breathe the product, use a mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com