

Thermal Insulation Reinforcement Mesh

PRODUCT DESCRIPTION

It is a fiberglass material with impregnated fiber layers against alkali and chemicals.

FEATURES

It prevents the sheathing plaster from disintegrating. It is alkali resistant. It is resistant to temperature changes.

It is easy to apply. It does not cause shrinkage or lumps.

PRODUCT INFORMATION

Chemical structure	: Glass fiber
Color	: Orange/White
Length	: 50 metre
Width	: 1 metre
Weight	: 160 gr/m ²

USAGE AREAS

It is used as a system component in BARS PROTHERM Thermal Insulation System.

APPLICATION INSTRUCTIONS

The product must be cut and prepared in advance according to the area to be used in the application. Joints should be overlapped by 10cm. After the first layer of PROTHERM SV is applied, PROTHERM TEX is embedded into the mortar by applying pressure to the intermediate layer before it dries. After the surface dries, the second layer of plaster is applied.

CONSUMPTION

1,10 m² / m²

PACKAGING

1 x 50 Metre

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions. Application should be made between +5 C and +30 C. Application should not be made in hot, rainy and windy weather. Application should not be made on surfaces at risk of frost. The product must be protected from rain, water, frost and negative external factors until it is cured.

915 PROTHERM TEX



Thermal Insulation Reinforcement Mesh

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a dry and cool (temperature between +5 C and +25 C) environment free of moisture. It should not be left under direct sunlight.

SAFETY

Do not breathe the product, use a mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com