

# 920 PROTHERM SD



## *Thermal Insulation Fixing Dowel*

### **PRODUCT DESCRIPTION**

It is a mechanical fastener used to fix PROTHERM EPS Thermal Insulation Boards to the facade.

### **FEATURES**

It provides the adhesion strength of thermal insulation panels against forces acting perpendicular to the surface, such as the vacuum effect of wind.

### **PRODUCT INFORMATION**

Size / Color : 10 cm / Blue

### **USAGE AREAS**

It is used as a system component in BARS PROTHERM Thermal Insulation System. It provides the adhesion strength of thermal insulation boards.

### **APPLICATION INSTRUCTIONS**

The thermal insulation plate is used after PROTHERM YP is applied to the wall.

### **CONSUMPTION**

6 pieces / m<sup>2</sup>

### **PACKAGING**

1 Pack of 500 Pieces

### **LIMITATIONS**

To obtain optimum quality, please adhere to the application instructions.

### **SHELF LIFE**

Store in a dry and moisture-free environment (temperature between +5 C and +25 C) in its original packaging from the date of production.

from 2 years. It should be kept away from moisture.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti  
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78  
Gürsu /BURSA TÜRKİYE  
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01  
www.barskimya.com info@barskimya.com

# 920 PROTHERM SD



## Thermal Insulation Fixing Dowel

### STORAGE CONDITIONS

It should be stored in its unopened original packaging in a dry and cool (temperature between +5 C and +25 C) environment free of moisture. It should not be left under direct sunlight.

### SAFETY

Do not breathe the product, use a mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

### LEGAL NOTES

*Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.*

*DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.*

*DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.*



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti  
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78  
Gürsu /BURSA TÜRKİYE  
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01  
www.barskimya.com info@barskimya.com