

Mesh Corner Profile

PRODUCT DESCRIPTION

It is an alkali-resistant, mesh corner profile for sheathing applications, used to strengthen weak areas (edges, corners, etc.) that are most easily affected by external influences and impacts.

FEATURES

It ensures smoother corners in cladding application.
It minimizes the damage from impacts.
It is easy to apply.

PRODUCT INFORMATION

Color : Orange/White
Size : 2.5 meters

USAGE AREAS

It is used as a system component in BARS PROTHERM Thermal Insulation System. It is used in building exterior corners, building interior wall corners and window centers.

APPLICATION INSTRUCTIONS

During PROTHERM SV application, the reinforcement mesh is placed in the corners where the joints overlap.

CONSUMPTION

0,25 mt / m²

PACKAGING

1 Pack of 50 Pieces

LIMITATIONS

To obtain optimum quality, please adhere to the application instructions.

SHELF LIFE

Store in a dry and moisture-free environment (temperature between +5 C and +25 C) in its original packaging from the date of production. from 2 years. It should be kept away from moisture.

925 PROTHERM FK



Mesh Corner Profile

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a dry and cool (temperature between +5 C and +25 C) environment free of moisture. It should not be left under direct sunlight.

SAFETY

Do not breathe the product, use a mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com