# 1005 BARS COLORATE



## **Coloring Tube For Plaster And Paints**

### PRODUCT DESCRIPTION

It is a coloring tube for white, water-based plasters, coatings and paints.

#### **FEATURES**

The coloring pigments in the tube have high coloring power. Rain, frost etc. It is resistant to exterior conditions. It is water repellent. It is easy to apply. It is semi matte. It is water-based and environmentally friendly.

### **USAGE AREAS**

In thermal insulation application on the exterior, it is colored and applied as a final coat.

### APPLICATION EQUIPMENT

Hand mixer - Steel Trowel

### **APPLICATION**

The product is ready for use. Remove the cap at the end of the tube of the color you choose and pour the pigment in the tube into the middle of the PROKREPI 1003 bucket. Some clean water is drawn into the tube again and poured into the bucket again. This process is applied 2 or 3 times until there is no pigment left in the tube. In applications to the same area, be careful to draw water at the same rate and the same number of times. Then, mix it with a low-speed mixer for 2-3 minutes until the color is completely homogeneous. To avoid tone differences, care should be taken to use products with the same charge number.

### **LIMITATIONS**

To obtain optimum quality, please adhere to the application instructions. Application should not be made in very high temperatures, direct exposure to sunlight, very windy or rainy weather. Application should not be made on surfaces at risk of frost. Application should be made between +5 C and +30 C. It should never be applied at temperatures below 5 C. The product should be protected from rain, water, frost and negative external factors until it cures.



# 1005 BARS COLORATE



## **Coloring Tube For Plaster And Paints**

### CONSUMPTION

1 tube of 1005 BARS COLARATE to color the light colored 1003 PROCREPI ,2 or 3 tubes of 1005 BARS COLARATE in dark colors

### **PACKAGING**

50 MI Plastic Syringe

### SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.

### STORAGE CONDITIONS

It should be stored in its unopened original packaging in a moisture-free, dry and cool environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.

These values were obtained as a result of laboratory experiments carried out in our company and are valid for the performance of finished applications at the end of the full drying period. Values may vary as temperature and humidity values in the construction site environment and application surfaces and areas will var  $_{V}$ 

#### **LEGAL NOTES**

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. \$\infty Ti. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.

