

1055 PROBAND 120



Waterproofing Chamfer Tape

PRODUCT DESCRIPTION

It is an alkali-resistant reinforcement mesh developed for waterproofing applications.

FEATURES

- It balances insulation product consumption.
- It is alkali resistant.
- It is resistant to temperature changes.
- It is easy to apply.
- It does not cause shrinkage or lumps.

PRODUCT INFORMATION

- Weight : 50 gr/ m²
- Size / Color : 1x100,00 mt / White

USAGE AREAS

It is used in BARS Waterproofing Systems.

APPLICATION INSTRUCTIONS

The product should be cut and prepared in advance according to the area to be used in application. The joints should be overlapped by 10 cm. After applying the appropriate waterproofing product in one layer, PROTEX is laid while the product is wet and embedded into the waterproofing product on the surface. The second or third layer of waterproofing is applied if necessary and the process is completed.

CONSUMPTION

1,10 m² / m²

PACKAGING

In Roll of 50 meters



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

1045 PROTEX



Waterproofing Chamfer Tape

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a dry, cool and moisture-free environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.

SAFETY

Do not breathe the product, use a mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com