

1060 PROBAND DLT



Dilatation Band 20-25-30-40

PRODUCT DESCRIPTION

It is a dilatation tape made of FPO used in the insulation of building joints and dilatation gaps in indoor and outdoor spaces.

FEATURES

Provides permanent waterproofing in dilatations.
It is easy to apply.
Can bridge cracks.

PRODUCT INFORMATION

Width : 25 metre
Roll Length : 20-25-30-40 cm

USAGE AREAS

It can be used with all liquid waterproofing products.

APPLICATION INSTRUCTIONS

The surface to be applied must be solid, dry, clean and free of loose parts.

The product must be mounted with PROMORTAR EPO or PROANKRAJ.

CONSUMPTION

1,00 mt / mt

PACKAGING

In Roll of 25 m

SHELF LIFE

It is 1 year from the date of production in its original packaging in moisture-free and dry environments (temperature between +5 C and +25 C). The mouth of the containers should be tightly closed when not in use. It should be kept away from moisture.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com

1060 PROBAND DLT



Dilatation Band 20-25-30-40

STORAGE CONDITIONS

It should be stored in its unopened original packaging in a dry, cool and moisture-free environment (temperature between +5 C and +25 C). It should not be left under direct sunlight.

SAFETY

Do not breathe the product, use a mask. Avoid contact with skin and eyes. Use protective gloves, glasses and clothing. In case of eye contact, consult a doctor immediately. Keep out of reach of children. In case of skin contact, wash with plenty of water and soap. Do not swallow. For detailed information and recommendations, please refer to the Safety Data Sheet.

LEGAL NOTES

Our technical data sheet is DEKOSTAR LTD., which has a wide range of usage areas. ŞTİ. It has been prepared to give general information about the products and to show the technical features of the products. It is a recommendation and this information is about the correct application, ground, air, equipment, etc. It is valid under the conditions and when the products are stored under the recommended conditions.

DEKOSTAR LTD. ŞTİ. Since it cannot control the conditions under which its products are used, it does not accept any responsibility for the application result and does not guarantee it. The user of the product must test its suitability before using the product.

DEKOSTAR San. will be liable for application errors that may occur if the product is used for purposes other than its intended purpose or if the application conditions and recommendations stated above are not followed. and Tic. Ltd. Ltd. is not responsible and has the right to change the features of its products without notice. Users should always refer to the latest edition of the Product Technical Data Sheet for the relevant product.



BARS KİMYA -Dekostar Yalıtım İnşaat San. ve Tic.Ltd.Şti
Gürsu Yeni Sanayi Alanı Karahıdır Mah. Okul Yolu Üzeri No:78
Gürsu /BURSA TÜRKİYE
Tel : (+90) 850 888 61 00 Whatsapp Gsm : (+90) 516 168 61 01
www.barskimya.com info@barskimya.com